PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

INTERNATIONAL APPLICATION TOBLIS		WO 060461
(51) International Patent Classification 6:	A1	(11) International Publication Number: WO 96/2463
C09B 43/16, C09D 11/00		(43) International Publication Date: 15 August 1996 (15.08.9
(21) International Application Number: PCT/GE (22) International Filing Date: 5 February 1996 (CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, P
(30) Priority Data: 9502341.2 7 February 1995 (07.02.95)		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt
(71) Applicants (for all designated States except US): A.G. [CH/CH]; Industriestrusse 15, CH-1701 Fribo MATTHEWS, Richard, Nordan (GB/GB); Ilford Town Lane, Mobberley, Knutsford, Cheshire W (GB).	xurg (Cl Limiu	f). [sd.
(72) Inventors; and (75) Inventors/Applicants (for US only): BAETTI [CH/CH]; Sur le Village, CH-1724 Prurom. JAN, Gerald [CH/CH]; Route du Bugnon 27, Villars-sur-Glare (CH).	an (Ci	n.
(74) Agent: MATTHEWS, Richard, Nordan; Ilford Limit Lane, Mobberley, Knutsford, Cheshire WA16 7JL		
(54) Title: DYES FOR INK JET PRINTING		
(57) Abstract		
There is described a new magenta azo dye which ca	un be us	ed in an aqueous composition in an ink jet printing process.
		•
-	-	
		_

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Affectio	GD	United Kingdom		
AT	Austria	GE	Georgia	MW	Malawi
ΑÜ	Australia	GN	Guinea		Mexico
23	Berbedos -	GR	Greece	NE	Niger
RE.	Beleisen	HE-	Hungary	NL	Netherlands
37	Berkina Fean	ir.	treiand	NO	Nariviy
BG	Belgaria	iT		NZ	New Zealand
M	Benin	ir Ir	italy	PL.	Poland
12	Brazil		Japan	PT	Portugui
BY	Belarma	ICE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystae	RU	Russian Federation
œ.		KP	Democratic People's Republic	SD	Sudan
œ	Central African Republic		of Koma	SE	Sweden
CH	Congo	KR	Republic of Korea	SG	Singapose
a	Sweatched	KZ	Kazakheran	51	Slovenia
CM	Côte d'Ivoire	u	Linchnensurin	SK	Slovakia
-	Cameroca	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swazikand
CS .	Czechoslovakie	LT	Lithungia	TD	Chail
œ	Czech Republic	u:-	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Desimert	MC	Monaco	Η̈́	Trinidad and Tobaco
	Emania	MD	Republic of Moldova	ÜA	Ultraine -
23	Spain	MG	Madagascar	UG	
Pl	Finland	ML	Mali		Uganda
/R	France	MIN	Mongotia	US	United States of America
GA	Gabon	MR	Maurania	UZ	Uzbekistan
				VN	Viet Nam

WO 96/24636 PCT/GB96/00300

Dyes for ink jet printing

Field of the invention

The present invention relates to dyes and aqueous ink compositions comprising these dyes for ink jet printing processes.

Ink jet printing systems generally are of two types: continuous stream and drop-on-demand. In continuous stream ink jet systems, ink is emitted in a continuous stream under pressure through an orifice or nozzle. The stream is perturbed, causing it to break up into droplets at a fixed distance from the orifice. At the break up point, the droplets are charged in accordance with digital data signals and passed through an electrostatic field which adjusts the trajectory of each droplet in order to direct it to a waste ink collecting vessel (e.g. for recirculation) or a specific location on a recording medium. In drop-on-demand systems, a droplet is expelled from an orifice to a position on a recording medium in accordance with digital data signals. A droplet is not formed or expelled unless it is to be placed on the recording medium.

The most important part of an ink used in ink jet printing are the dyes. Although a number of dyes have been proposed non has been produced which meets all the requirements of a modern printing process.

Background of the invention

Reactive dyes with incorporated 1,3,5-triazine structural elements are common in textile printing and have also been proposed for ink jet printing. Such dyes are for several reasons in general not too well suited for this application. The reactive groups are not very stable over prolonged periods in aqueous solutions. Dyes containing such reactive groups are moreover, due to their potential health risk, less suitable for handling in a non industrial environment. Non reactive dyes of this kind have been described in USP 4:771129

(K. Hideo) and USP 4'777'248 (D. Greenwood). In particular dyes of the following structural formulas have been described:

USP 4'771'129 (dye 5)

(1)

USP 4'777'248 (dye 1)

(2)

In some of these dyes particularly enhanced water-solubility has been claimed to be due to the introduction of elements of the following structure

1)

and in some cases water solubility seems still to be improved by introduction of elements of the structure

(USP 4'777'248) into the triczine part of the dye.

These dives are however still inadequate when used in aqueous inks of modern ink jet printers. In particular printers of the continuous-stream type are highly demanding as far as physical properties of the inks are concerned. Particularly critical are storage stability of the inks without forming degradation products prone to clog the nozzles of the printer. Printers are today able to print images of high density rapidly. Therefore highly concentrated inks are needed in order to avoid the jetting of high water volumes onto the receiving layer. These high concentrations should ideally, for environmental reasons, be achieved without the use of organic cosolvents. Such inks can only be prepared with dives having a particularly high water solubility.

Dyes of the above mentioned structures which are the state of the art, are in general not soluble enough to satisfy the required demanding conditions. It is the aim of this invention to provide dyes with the required high water solubility.

Description of the invention

This invention relates to azo dyes of the formula (4)

wherein:

R₁ is selected from hydrogen or an aliphatic radical having from 1 to 6 C atoms:

(4)

n is 2, 3 or 4;

X is NR₃R₄ where

 R_3 and R_4 are independently selected from hydrogen, alkyl from 1 to 6 C atoms, C2 to C6 substituted alkyl where the substituents are selected from OH, OCH₃, COOM, SO₃M; aratkyl; unsubstituted aryl or an aryl substituted by COOM or SO₃M;

 R_3 and R_4 may form a ring without or with inclusion of a hetero atom;

Of

is SR5 in which R5 is alkyl from 1 to 6 C atoms, C2 to C6 substituted alkyl where the substituents are selected from OH, OCH3, COOM, SO3M;

Of

- is OR₆ in which R₆ is hydrogen or an aliphatic radical having from 1
 to 6 C atoms;
- is hydrogen, alkyl of 1 to 6 C atoms, C2 to C6 substituted alkyl where the substituents are selected from CN, COOM, OH, COOCH₃, COOCH₂CH₃, COCH₃; unsubstituted anyl or anyl substituted by CH₃, halogen;
- is hydrogen, a metal atom, an ammonium or ammonium substituted with alkyl, alkoxyalkyl and hydroxyalkyl each having 1 to 12 C atoms.

The azo dyes of the present invention comprise no reactive groups. They are of particular use in inks used for ink-jet printing because of their high water solubility.

Dye Synthesis

One method of preparing dyes of the present invention is by

(f) Reacting the known (USP 3'787'215) monoazo compound of formula (5)

with cyanuric chloride under conditions such that one chlorine atom of the triazine is displaced by the monoazo compound of formula (5) then

(ii) reacting the mono-substituted dichloro-triazine with a compound of formula (6)

(6)

under conditions such that a second atom of chlorine is displaced by the compound of formula (6) and

(iii) reacting finally the di-substituted triazine with a compound XH under conditions that the third chlorine atom is displaced by X.

Where X is a compound of formula (6), the second and third chlorine atoms of the triazine nucleus may be replaced simultaneously.

The present invention is illustrated by the following example.

Example 1

Preparation of the compound No. 100 (Na-satt)

step 1

48.3 g (0,1 mol) monoczo compound (5) was added to water (600 ml) and the pH adjusted to 8 by addition of 30 % aq. sodium hydroxide solution.

A solution of cyanuric chloride (20.3 g, 0,11 mol) in ethyl acetate (100 ml) was added maintaining the pH at 7 to 8 and the temperature at $15 - 20^{\circ}$ C. After 30 minutes a solution of 2-aminoethane-sulfonic acid, sodium salt (17.8 g, 0,12 mol) in water (120 ml) was added to the reaction mixture while maintaining the pH at 7 - 7.5 and the temperature at 30° C. After 30 minutes the reac-

tion mixture was heated to 50° C and stirred for 1 hour at this temperature, cooled to room temperature and then the product was filtered.

step 2

The wet product (200 g) from step 1 was added to a solution of 1-methyl-2-pyrrolidinone (200 ml) and 2-(methylamino)ethanol (18 g, 0.24 mol). The reaction mixture was heated to 90° C for 3 hours and cooled to room temperature. A solution of 12 g of sodium acetate in ethanol (400 ml) was added to the reaction mixture. The solid was collected by filtration, washed with ethanol (300 ml), dried in vacuum at 60° C to yield the magenta dye (64 g) of formula No. 100.

in an analogous manner using appropriate starting materials the dyes described in Tables 1 and 2 can be obtained.

The dyes of general formula

were made wherein the substituents are:

Compound No.	X	М	λ max (nm) in H ₂ O
100	N(CH ₃)CH ₂ CH ₂ OH	Na	519
101	N(CH2CH2OH)2	Na	518
102	NHCH2CH2SO3Na	Na	516
103	S(CH ₂) ₃ SO ₃ K	К	518
104	SCH ₂ CH ₂ OH	Na	516
105	ОН	Na	516
106	SCH ₂ COOK	К	517
107	OCH ₂ CH ₃	Na	515

<u>Table 1</u>

The dyes of general formula

were made wherein the substituents are:

Compound No.	R7	X	М	λmax (nm) in H ₂ O
200	CH ₂ CH ₂ CN	N(CH ₃)CH ₂ CH ₂ OH	Na	528
201	CH ₂ CH ₂ CN	SCH ₂ CH ₂ OH	Na	526

Table 2

Example 2

The dyes of the present invention are specially adapted for the preparation of inks. Inks for ink jet printing are well known. These inks consist in essence of a liquid vehicle dissolved therein a dye. The liquid vehicle of the inks employed for the printing consists in general of water or a mixture of water and a miscible organic solvent such as C1-C4 alkanols, alkylene glycols such as di(propylene glycol), di(ethylene glycol), polyols such as 1,5-pentanediol, gycerol, 1,2,6-trihydroxyhexane, nitrogen-containing solvents such as 2-pyrrolidinone, N-methyl-2-pyrrolidinone, 1-(2-hydroxyethyl)-2-pyrrolidinone, 1,3-dimethyl-2-imidazolidinone, 1,1,3,3-tetramethylurea or sulfur containing solvents such as organosulfoxides, sulfolane and the like.

The non water parts of the printing ink generally serve as humefactant, cosolvent, viscosity regulating agent, ink penetration additive, levelling agent or drying agent.

In addition aqueous inks may contain miscellaneous known additives like viscosity modifiers, such as cellulose derivatives and other water-soluble resins, various kinds of surfactants, surface tension modifiers, optical brighteners, UV absorbers, light stabilisers, biocides and pH conditioners, such as buffers. Inks for use in ink jet recording of the type based on continuous-stream usually contain an inorganic salt as electrolyte, such as sodium/ammonium/lithium halogenides or sulphate.

This description of inks is for illustration only and is not to be considered as limiting the invention.

The present invention in so far as it relates to inks is further illustrated with reference to the following examples in which all parts and percentages are by weight.

Inks were prepared, using the dyes 100 to 102, as described above, according to the following recipe:

dye	ó parts
glycerol	20 parts
water	74 parts

The inks were prepared by dissolving the ingredients and filtering the solution under pressure through a Millipore filter (0,5 micron).

The inks were tested and shown to satisfy all the requirements specifying a usable ink. In particular they were shown to meet the following criteria:

- (1) Physical properties of the ink, such as viscosity, conductivity and surface tension, are each within a defined range.
- (2) All dyes have good solubility in the ink medium to give solutions having good stability which do not plug the fine ejecting orifices.
- (3) The recording agent gives images of sufficient optical density.
- (4) The ink does not change physical properties or deposit solid matter during storage.

WO 96/24636 PCT/GB96/00300

(5) Printing can be performed without a restriction on the nature of substrate.

-11-

- (6) The ink exhibits a high rate of fixation.
- (7) The ink gives images of good resistance to water, light and abrasion.

Example 3

The solubilities of the dyes according to the invention were determined as follows:

An excess of dye was heated at 50° C in water with stirring for one hour. The mixture was then cooled down to 20° C and filtered, and the dye content of the clear solution was determined spectroscopically. The results obtained are shown in table 3

Dye No	Solubility (in g per 100 ml)
100	35
101	32
102	26
dye 1	20
dye 5	15

Table 3

The dyes 1 and 5 are known from USP 4'777'248 and USP 4'771'129 es heretofore set forth.

The results in table 3 show the significantly higher solubility of the dyes according to the invention compared to dyes of the prior art.

CLAIMS:

1. An azo dye of formula (4)

MO₃S

$$N=N$$
 $N=N$
 $N=N$

wherein

R₁ is selected from hydrogen or an aliphatic radical having from 1 to 6 C atoms;

n is 2,3 or 4;

X is NR₃R₄ where

 R_3 and R_4 are independently selected from hydrogen, alkyl from 1 to 6 C atoms, C2 to C6 substituted alkyl where the substituents are selected from OH, OCH3, COOM, SO₃M; aralkyl; unsubstituted anyl or an aryl substituted by COOM or SO_3M ;

 R_3 and R_4 form a ring without or with inclusion of a hetero atom;

or

is SR5 in which R5 is alkyl from 1 to 6 C atoms, C2 to C6 substituted alkyl where the substituents are selected from OH, OCH3, COOM, SO3M;

stituted with alkyl,alkoxyalkyl and hydroxyalkyl each having 1

2. An azo dye according to claim 1 where

to 12 C atoms.

R₁ is hydrogen and where

X, n, R₃ to R₇ and M are as set forth in claim 1.

- 3. An azo dye according to claim 2 where
 - n is 2 or 3:
 - R3, R4 are independently selected from hydrogen, C1 to C6 alkyl, C2 to C6 substituted alkyl where the substituents are selected from OH, OCH3, COOM, SO3M or R5, R6 form a 5- or 6-membered ring without or with inclusion of a hetero atom;
 - R5 is a C1 to C4 substituted alkyl where the substituents are selected from OH, COOM or SO₃M;
 - R6 is hydrogen, CH3 or CH2CH3;
 - R7. M are as set forth in claim 1.

An azo compound according to claim 3 where

is selected from hydrogen, C1 to C3 alkyl or C2 or C3 substituted alkyl where the substituents are CN or COOM.

5. An azo dye according to claim 4 where

R₅ is CH₂CH₂OH, CH₂COOM or (CH₂)₃SO₃M;

Ro is hydrogen:

M is hydrogen, alkali metal atom, ammonium or ammonium substituted with C1 to C2 alkyl or with CH2CH2OH.

6. An azo dye according to formula (7)

(7)

where

R3.R4 are independently selected from hydrogen or C2 to C3 substituted alkyl where the substituents are selected from OH. COOM or SO3M;

R7 is hydrogen. CH2CH2CN or CH2CH2COOM and M is hydrogen, alkali metal or ammonium ion.

and the second s

7. An ink comprising a dye or a mixture of dyes as described in anyone of claims 1 to 6.

-15-

8. An ink which contains in addition to a dye or dyes as claimed in anyone of claims 1 to 6 one or more other dyes.

	INTERNATIONAL SEARCH REP	ORT b MAPP	ecston No
		PCT/GB 96	/00300
A. CLASSI IPC 6	FICATION OF SUBJECT MATTER C09B43/16 C09D11/00		
According to	o international Patent Classification (IPC) or to both national classific	estion and IPC	
B. FIELDS	SEARCHED OCCUMENTATION SERVING (CLASSIFICATION SYSTEM followed by classification	in symbols)	
IPC 6	C89B C89D		
Documental	on marched other than manuscum documentation to the others that m	ich documents are included in the fields (earched
Electronic d	ata base constitut during the international search (name of data base	and, where practical, search terms used)	
	AND COLUMNS ON THE RESIDENCE OF THE STATE OF		
C. DOCUM	IENTS CONSIDERED TO BE RELEVANT Otation of decimant, with indication, where appropriate, of the rel-	Culty beggings	Relevant to class No.
· ·			
X	EP,A,0 187 520 (ICI PLC) 16 July see page 4, line 24 - line 31; exa & US.A.4 777 248 (D.GREENWOOD) cited in the application	1986 ample 4	1-8
A .	EP.A.0 194 885 (TAOKA CHEMICAL CO ;SUMITOMO CHEMICAL CO (JP)) 17 Se	LTD ptember	1-8
	1986 cited in the application see page 6, line 3 - line 6; claim		
A	DE.A.22 58 837 (AGFA GEVAERT AG) 1974 see compounds 1-3; claim	12 June	1-8
A	US.A,3 142 669 (J.F.FEEMAN) 28 Ju see column 3, line 58 - column 4, example 32	ly 1964 line 7;	1-6
<u> </u>			
Fu	ther documents are tuned in the continuation of box C.	X Palent (amily members are lated	in 400(1.
.V. 4000	nest defining the paneral state of the art which is not	T later document published after the at or priority date and not in conflict to cand to understand the principle or	MRI Alle Substantian con
E, caspe	dered to be of perfectler relevance r document but published on or efter the unterestional	"X" document of particular relevance; the case to be considered novel or case	e claimed invention of he considered to
1.11	and the state of t	SINGLE SE CHARGE AS SUB-ACIED ON A	e clamed invention
out of	ou ou other absorty revenu (in absorped) It is cases to estrupting the becausesou seem or experien.	cannot be considered to severy an	more other such docu-
other	ment referring to an oral disclosure, use, exhibition of the second section of the sec	ments, such combination being over th the art.	tota en a besette granen
"P" docum	ment published prior to the international filing date but then the priority date classed	'A' document member of the same pate	
Date of th	e actual completion of the usernational starch	Date of making of the international	see of the
	23 May 1996	0 6 -08- 199	6
Name and	making address of the ISA	Authorized officer	

Ginoux. C

ij

1

INTERNATIONAL SEARCH REPORT

by val Apphication No PCT/GB 96/99399

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0187520	16-97-86	JP-B- 60498. JP-A- 611639 US-A- 47772 US-A- 47268	67 24-07-86 48 11-10-88
EP-A-0194885	17-09-86	JP-A- 6215610 US-A- 477112	
DE-A-2258837	12-86-74	FR-A,B 220879 GB-A- 145587 JP-A- 4908953 SE-B- 39540 US-A- 388927	77 17-11-76 34 27-98-74 56 15-98-77
US-A-3142669	28-07-64	NONE	•